



Filter type:	<b>NW500</b>
Connexion diameter:	2"
Average flow rate (m <sup>3</sup> /h):	18 at ΔP 0,2 bar
Working pressure (bar):	10
Max. operating pressure (bar):	16
Max. operating temperature (°C):	50
Weight (kg):	6,4 / 8 (with packaging)
Packaging in mm (L x W x H):	770 x 320 x 240
Quantity / pallet (units):	21
Air drain screw:	Polyamide (PA) + polyester (2K)
Filter head:	Polypropylene (PP) + 20% GF
Bowl:	SAN
Wrench:	ABS
Connections:	PA
Nuts:	PP + 20% GF
Seals:	O-ring butadiene-acrylonitrile (NBR)
Centrifugal vane + cap:	Polypropylene (PP) + 20% GF + elastomer (2K)
Filtering support:	PP + 20% GF
Valve adapter:	PA
Filtering sleeve:	Polyester (non-washable) or nylon (washable)
Filtration surface (cm <sup>2</sup> ):	1288
Original equipment:	Filtering sleeve 25 μm, wrench, drain-cock ¼ " nickel-plated brass, 2 pressure gauges with glycerine 0-20 bar ¼ " brass + 2 connections 2"
Option:	Stainless steel wall fixation 3 mm
Filtering fineness available (μm):	Non-washable : 1 - 5 - 10 - 25 - 50 - 100
(packs of 5 sleeves)	Washable : 150 - 300

